

INDUSTRIAL AND TEXTILE DETERGENTS, INC.

www.itdinc.biz

EMAIL: ADMIN@ITDINC.BIZ

1827 AUGER DRIVE TUCKER, GA 30084

TOLL FREE: (800) 472-1233

FAX #: (770) 939-5704

DECK STRIPPER

PRODUCT CODE

22521 Deck Stripper

SIZES AVAILABLE

22521-01CS 4 gallon case

Weighs 40 lbs.

22521-05 5 Gallon Container

Weighs 50 lbs.

22521-55 55 Gallon Drum

Weighs 520 lbs.

22521-1DK 1 Drum Kit

Weighs 105 lbs.

22521-5DK 5 Drum Kit

Weighs 495 lbs.

TECHNICAL INFORMATION

Color: Clear pH Concentrate: 13.7 Odor: Odorless 1% 12.4



DECK STRIPPER is a concentrated, heavy-duty formulation to penetrate and emulsify dirt, grease, oil, paint, and stain. This product is for use on wood and concrete surfaces. It will work in cold water as well as hot water, and rinse free at any temperature

DIRECTIONS FOR USE: The optimum cleaning dilution for most surfaces is between 1:2 and 1:4. When stripping paint, stains and sealers use at full strength. Thoroughly wet the entire area to be cleaned. Broom out any puddles of water. Spray solution on with a lowpressure applicator, let stand to penetrate for ten minutes. Stubborn areas of layered paint may require brushing and a reapplication of DECK STRIPPER. Rinse with low pressure to avoid damage to wood, high -pressure rinse on concrete. DO NOT USE ON POLISHED OR ANODIZED ALUMINUM. DO NOT USE ON ANY ALUMINUM OR ANY PAINTED SURFACES NOT WISHING TO STRIP. DO NOT ALLOW TO DRY ON SURFACES. ALWAYS RINSE THOROUGHLY.

CONTAINS: Sodium Hydroxide Neutralize wood rinsing with an application of WOOD BRIGHTENER after stripping. Refer to Product No. 60770.

CAUTION: Do not allow to freeze. Do not store at temperatures above 120° F. Keep out of the reach of children. Use eye, face and hand protection when handling. For industrial use only