



CONSISTENT QUALITY PRIVATE LABELING PROMPT & DIRECT SHIPMENTS

www.itdinc.biz

1827 Auger Drive  
Tucker, Georgia 30084

Toll Free: (800) 472-1233

email: admin@itdinc.biz

Fax #: (770) 939-5704

## ALUMINUM WELD CLEANER & BRIGHTENER

### PRODUCT CODE

16720

### SIZES AVAILABLE

16720-05 5 Gallon Container

➤ Weight: 50 lbs.

16720-55 55 Gallon Drum

➤ Weight: 500 lbs.

### **CAUTION:**

**CONTAINS HYDROFLUORIC ACID, all exposures are considered severe. Avoid contact with skin and eyes. Use with adequate ventilation. OSHA requires use of skin and eye protection. Do not allow to freeze. Do not store at temperatures above 120° F. Keep out of the reach of children. For industrial use only.**

### **PHYSICAL DATA**

Appearance: [Clear blue](#)

Odor: astringent



**ALUMINUM WELD CLEANER & BRIGHTENER:** Is formulated for aluminum and stainless steel trailers. Do not use on other surfaces such as aluminum wheels or aluminum engine blocks. If splashed on glass, wash off immediately.

**DIRECTIONS FOR USE:** May dilute with water before using. Mix solution in a plastic or stainless steel bucket or sprayer. Make up only enough solution for the job at hand.

**For Cleaning Trucks and Trailers:** Under average conditions of temperatures (55-85°F) and relative humidity (50%), a solution of 1 part concentrate with 1 part water will give good results. Since lower temperatures slow cleaning action use a stronger solution on cool days. **Note:** Working in hot direct sun may cause streaking-wet down sides of trailer to cool surface before applying. Whenever possible, it is better to work in the shade. **To Apply:** Always work from the bottom up to avoid streaking and also work only small areas so surface does not dry before rinsing. Spray product after solution has set for about 15 seconds; flush thoroughly with water, being sure to rinse adjacent concrete ramps, floors, and drains.

**DO NOT RUN THROUGH PUMPING SYSTEM OR HEATING COILS**