

CAT5 ENHANCED 350MHz STP CMR RATED (SHIELDED)

Cat5eCableGuy.Com

DESCRIPTION

Category-5E, 24AWG, STP, 8C Solid Bare Copper, CMR Rated, PVC Jacket 1000ft.

FEATURES

- High-Performance Data Cable
- 350MHz Bandwidth for Data Applications, Fast Ethernet and 155Mbps TP-PMD/CDDI
- Category-5E Shielded Twisted Pair
- Easily Identified Color-Striped Pairs
- 24AWG Stranded Copper Conductors
- Exceeds TIA/EIA-568B.2-1, ISO/IEC 11801
- Riser Rated PVC Jacket
- ETL Listed
- 1000ft Pull Box



Dimensions 16.5H x 16.5L x 8.5W (inches)
45pcs per pallet
(Packaging may vary)

Technical Data

Rated Temperature (°C)	75
Product Standard Certification	CMR
Application	Horizontal Wiring in LAN
Reference Standard	EIA/TIA 568 & ISO/IEC 11801

Conductor

Size **Solid Bare Copper**

24 AWG

Insulation

PE

Average Thickness (mm) 0.228

Min. Point Thickness (mm) 0.205

Insulation Diameter (±0.005mm) 0.97

Twisted Pair Diameter (±0.01) 1.94

Bond (mm) PE-Tape

Shield (mm) AL Foil

Drain Wire Dia.(±0.003mm) 0.40

(Solid Tinned Copper)

Assembly Diameter

4.95

Jacket

PVC

Average Thickness (mm) 0.60

Min. Point Thickness (mm) 0.55

Outer Diameter (±0.10mm) 6.15

Rip Cord Yes

Color of Pairs

Pair 1	Blue,White-Blue
Pair 2	Orange,White-Orange
Pair 3	Green,White-Green
Pair 4	Brown,White-Brown

Marking on Jacket

VERTICAL 4001453 cETLus VERIFIED CMR FT4 STP 4PR
24AWG CAT5E 350MHz TIA/EIA-568B.2 RoHS XXXFT
(SEQUENTIAL FOOT MARKERS ON JACKET)

Jacket color available in
Blue, Black, White, Green, Gray, Red, Yellow



Cat5eCableGuy.Com
Where Quality Cable is on Sale!



Rev. 01/2011

Subject to change without notice.

CAT5 ENHANCED 350MHz STP CMR RATED (SHIELDED)


PERFORMANCE

Electrical Characteristics:

1.0-100MHz Impedance (Ohms)	100±15
100-200MHz Impedance (Ohms)	100±25
200-350MHz Impedance (Ohms)	100±35
1.0-350.0MHz Delay Skew (ns/100m)	<=45
Pair-to-Ground Capacitance Unbalance (pF/100m)	<=330
Max. Conductor DC Resistance 20°C (ohms/km)	93.8
Resistance Unbalance (%)	<=5
Voltage Rating	220V-300V
Max Current	10mA

Frequency (Mhz)	Return Loss (Min dB)	Attenuation Max	Next (ns/100m)	ACR Typ(dB)
0.772	19.4	1.8	67.0	67.7
1	20.0	2.0	65.3	67.3
4	23.0	4.1	56.3	56.2
8	24.5	5.8	51.8	50.0
10	25.0	6.5	50.3	47.8
16	25.0	8.2	47.3	44.0
20	25.0	9.3	45.8	41.5
25	24.3	10.4	44.3	38.9
31.25	23.6	11.7	42.9	36.2
62.5	21.5	17.0	38.4	27.4
100	20.1	22.0	35.3	19.3
200	18.0	32.4	30.8	3.5
300	16.8	41.0	28.2	-----
350	16.3	44.9	27.2	-----

Frequency (Mhz)	PSNext (Min dB)	ELFEXT Min(db/100m)	PSELFEXT Min(db/100m)
0.772	64.0	66.0	63.0
1	62.3	63.8	60.8
4	53.3	51.7	48.7
8	48.8	45.7	42.7
10	47.3	43.8	40.8
16	44.3	39.7	36.7
20	42.8	37.7	34.7
25	41.3	35.8	32.8
31.25	39.9	33.9	30.9
62.5	35.4	27.8	24.8
100	32.3	23.8	20.8
200	27.8	17.7	14.7
300	25.2	14.2	11.2
350	24.2	12.9	9.9



Cat5eCableGuy.Com
Where Quality Cable is on Sale!

Rev. 01/2011

Subject to change without notice.