

SoniVox® Plus™ Amplifier Instructions

Instructions

Please read this entire instruction sheet prior to operating the SoniVox® Plus™ Amplifier system. We recommend you keep these instructions for future reference.

Kit Components

SoniVox® Plus™ Amplifier, 5v power supply, Headset microphone, Neck Strap

Extra Accessories (sold separately)

Auxiliary cable, Auxiliary extension cable, Clip on Microphone

Neck Strap Installation

- 1) Remove the included neck strap from the kit and slide each end of the strap through the sliver side slots on the amplifier and back up through the adjustment pieces on the sides of the strap.
- 2) Adjust the strap to desired height and comfort.

Charging Instructions

NOTE:

The rechargeable Battery in this kit requires a full 10 hour charge before use.

- 1) Plug the power supply into a wall outlet. The LED on the power supply will illuminate red while it is plugged in and is receiving power.
- 2) Locate the micro USB port labeled CHARGE; plug the included power supply into this port. The LED will illuminate red while the battery is charging.
- 3) The LED will illuminate green when the battery is fully charged.

Microphone Installation

Locate the microphone jack on the amplifier (labeled MIC). Choose one of the microphones included in the kit and insert the plug into the MIC jack. NOTE: For best results, we recommend the headset microphone, especially for use by Laryngectomees. This microphone should be placed near the lips.



SoniVox® Plus™ Amplifier Instructions

Operating Instructions

- 1) Plug-in an included microphone and place it accordingly.
- 2) Turn the amplifier on by Pressing the **Power(Push)** knob down until the blue LED illuminates.
- 3) Adjust to desired volume by rotating the Power(Push) knob.

Troubleshooting

oubleshooting	
Trouble	Solution
No Sound	 Turn amplifier ON. Ensure microphone is fully connected to MIC jack. Try another microphone.
No Blue Light when amplifier ON	 Repress the Power(Push) knob. Charge the amplifier.
Distortion	 Replace microphone. Ensure microphone is fully connected to MIC jack.
Feedback (squealing)	 Ensure microphone element is pointed away from amplifier speaker. Reduce amplifier volume. Ensure microphone is close to your upper lip. Direct amplifier away from microphone.
Installing neck strap	Use a toothpick to help get the strap through the sliver slot.

Warranty

The Griffin Laboratories Limited Warranty covers manufacturer defects in materials and workmanship. Coverage is for 1 year on the SoniVox® Plus™ amplifier, 90 days on included accessories.