



# Domino<sup>®</sup> Neutron Detector D411S-30-D25-V5.4

## Solid-State Neutron Detection Applications

Neutron detector applications include those for homeland security (e.g., border screening), fundamental research (e.g., at neutron scattering beamlines), and industrial monitoring (e.g., personnel monitoring, water content in soil). Solid-state neutron detectors provide an alternative to the <sup>3</sup>He-based detectors, maintaining a high thermal-neutron detection efficiency, at a fraction of the volume, mass, voltage, and power required from gas or liquid detectors.

## The RDT Domino<sup>®</sup>

A strong demand for thin form-factor neutron detectors with the flexibility to adjust available detection area has driven RDT to offer the end-to-end pluggable Domino<sup>®</sup> with 4-cm<sup>2</sup> detection area, 20% to 30% thermal-neutron efficiency, less than 0.3-mW power consumption, and digital output per module. The digital outputs of the Domino<sup>®</sup> may also be tied together in the tiled format.

## MSND<sup>®</sup> Technology


The detector utilizes microstructured semiconductor neutron detector (MSND<sup>®</sup>) technology<sup>‡</sup> with <sup>6</sup>Li conversion to yield an adjustable thermal-neutron detection efficiency of up to 30%. Optimum HDPE moderator for <sup>252</sup>Cf neutron source at 1-m is 3-4 cm in front and 3-6 cm behind the MSND<sup>®</sup> sensor.

## Electronics & Interfacing

The onboard electronics package includes a preamplifier, shaping-amplifier, discriminator, analog-to-digital converter, temperature sensor, and voltage regulator.


## Specifications

Detector Area: 4 cm <sup>2</sup>	Pulse width: 5-50 μs
ε <sub>thermal</sub> : 30(±1)%@ 20°C	γ-reject: 1:10 <sup>7</sup>
ε <sub>Cf-252</sub> : 0.04%(no mod)	Mass: 9.5 grams
ε <sub>Cf-252</sub> : ~0.1%(1in. <sup>3</sup> mod)	Pileup limit: <33 kcps
I <sub>cont</sub> : 120 μA	Rad Hard: <10 <sup>10</sup> Rads/s
V <sub>input</sub> : 2.9-5.5 V	Deadtime: 150 μs
V <sub>output</sub> : 2.7 V (≥1kΩ)	Tileable: yes, 1-D



Website: [www.radectech.com](http://www.radectech.com)  
 Custom Inquiries: [bellinger@radectech.com](mailto:bellinger@radectech.com)  
 Distributor: [www.rotundascitech.com](http://www.rotundascitech.com)

Built in Temperature Sensor  
 Sensitivity to Ambient Light : No  
 Temp. Range: -40°C to 55°C  
 Connector: Samtec (2mm Center)  
 TMM-110-01-L-S-RA-004 (male)  
 SQT-110-01-L-S-RA-007 (socket)





# Domino® Neutron Detector D411S-30-D25-V5.4


## Electronic Specifications

If provided power is particularly noisy, decouple the power to local ground as close as possible to the connectors (ceramic in parallel with a tantalum is always best and a series bead never hurts). Be sure to use all ground pins (tie to a plane if possible). Do not tie anything to the "Do not connect" pins. Some are used for internal diagnostics during the test process and connections may cause device failure.

Pin #	Domino® V5.4	
	J1 MAIN CONNECTOR (Samtec TMM-110-01-L-S-RA-007)	J2 CASCADE CONNECTOR (Samtec SQT-110-01-L-S-RA-007)
1	DO NOT CONNECT	DO NOT CONNECT
2	GROUND	GROUND
3	GROUND	GROUND
4	+VDC INPUT (+2.9 VDC MIN. +5.5 VDC MAX)	+VDC CASCADE OUT
5	+VDC INPUT (+2.9 VDC MIN. +5.5 VDC MAX)	+VDC CASCADE OUT
6	SDA (+2.7 VDC)	DO NOT CONNECT
7	POLARITY KEY (CLIPPED PIN)	POLARITY KEY (PLUGGED SOCKET)
8	SCL (+2.7 VDC)	DO NOT CONNECT
9	PULSE OUT (DRIVEN - LV CMOS +2.7 VDC)	DO NOT CONNECT
10	PULSE OUT (CASCADE - OPEN DRAIN W/O INTERNAL PULL-UP)	PULSE IN CASCADE

## Accessories

- ❑ *USB Driver Board:* A great way to quickly test the Domino® detector in your lab. Connection and power is made via a standard USB Micro AB connection and interface software is provided to collect counts for a specified time period.
  
- ❑ *Panel Array Readout Motherboard:* Another way to panelize the Dominos® into an array. Individual Domino® strings can be readout individually or as a single unit.



# Domino<sup>®</sup> Neutron Detector




## Radiological Sensitivity Specifications

All measurements were performed with detectors irradiated with an ANSI-Moderated Cf-252 source at 0.25-m from the source, and compared directly to the vendor-listed calibrated He-3 neutron detector.

Model	Detector Type	Gamma-ray Reject Rate	Neutron Sensitivity	Measured Cf-252 Response	Power Req. (mW)
<b>D411S-20-D25-V5.4</b> RDT Domino <sup>®</sup> Version 5	Semiconductor-based detector w/ MSND <sup>®</sup> Technology	< 1-cpm at 75 mR/h with a Cs-137 Source; has increased gamma-ray rejection	0.8 cps/nv ± 0.04 cps/nv [20% Th. Eff.]	0.475 cps	0.3-mW at 3V
<b>D411S-30-D25-V5.4</b> RDT Domino <sup>®</sup> Version 5	Semiconductor-based detector w/ MSND <sup>®</sup> Technology	< 1-cpm at 50 mR/h with a Cs-137 Source	1.2 cps/nv ± 0.04 cps/nv [30% Th. Eff.]	0.729 cps	0.3-mW at 3V
<b>Two (2) Dominos Tiled</b> <b>D411S-30-D25-V5.4</b> RDT Domino <sup>®</sup> Version 5	Semiconductor-based detector w/ MSND <sup>®</sup> Technology	< 1-cpm at 50 mR/h with a Cs-137 Source	2.4 cps/nv ± 0.08 cps/nv [30% Th. Eff.]	1.417 cps	0.6-mW at 3V
<b><u>He-3 Neutron Detector Comparison</u></b>	He-3 Gas-Filled Detector at 10-atm  Dimensions: 0.75-in. dia. by 3-in. length	Not Reported. Measured at < 1-cpm at 50 mR/h with a Cs-137 Source.	Reported as: 5.3 cps/nv	3.175 cps	N/A, depends on the ancillary readout electronics.

SAMTEC #SQT-110-01-L-S-RA-007

SAMTEC #TMM-110-01-L-S-RA-004





1 of 4: 1-cm<sup>2</sup> MSND Sensor

Digital Readout Electronics

3.45 ± 0.25

2.70 ± 0.15



**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Radiation Detection Technologies, Inc. (RDT). ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF RDT IS PROHIBITED.

<b>Address:</b> 4615 S. Dwight Dr. Manhattan, KS 66502	UNLESS OTHERWISE SPECIFIED:	DATE	Radiation Detection Technologies, Inc. TITLE: Domino V5.4		
	DIMENSIONS ARE IN: <b>Millimeter (mm)</b>	DRAWN (UPDATED) 6/19/2019			
<b>Contact:</b> Steven Bellinger <b>email:</b> bellinger@radectech.com <b>Tel:</b> O:(785) 532-7087	Material:	<b>COMMENTS:</b> Solid-state Neutron Detector Total Detector Area: 4-cm <sup>2</sup> Pulse width: 5-50 μs eth. : 30(±1)%@ 20°C	SIZE	DWG. NO.	REV
			<b>A</b>	D411S-30-D25-V5.4	01
			SCALE: 1:1	WEIGHT:	SHEET 1 OF 1