# Portable Utility Lights

## 4 Sources of Light Sources



**LED 37** 

- 30,000+ hour lamp life
- · Safety glass front lens cover
- NEMA 4 rated enclosure
- · Can be used with pedestal, cart, and tripod mounts only.
- Compliant with RoHS 2 Directive (2011/65/EU).



Intertek







Fluorescent

· Shade remains Cool-to-the-

bulbs (included)

Touch.






- Weatherproof aluminum diecast light heads
- 500 Watt quartz bulbs (included).


- · Longest Lamp Life
- Lowest energy usage per lumens produced.

LED 1 & 2

- 12 Watt LED bulbs (included)
- Shade remains Cool-to-the-Touch.

## 6 Types of Bases and Mounts





#### • 16 gauge round steel tube construction Height adjustable from 5' to 8' high • 10" diameter wheels

TRI

#### Tripod Base

- · 20 gauge round steel tube construction
- Height adjustable from 3' to 6'- 6" high
- Base covers 46" diameter



#### Floor Base

- 12 gauge steel base
- · Handle included
- · Base covers 16" diameter area



Clamp secures light head to most surfaces up to 3"

Clamp-On Mount




#### Magnet Mount

- 210 lb. magnetic strength
- 1/4" steel arm
- Extends 6" from mounting surface

## Light Selection Chart & Illumination Levels

LIGHT SOURCE:			QUARTZ HALOGEN		FLUORESCENT		LED		LED 37	
# OF LIGHT HEADS			2	1	2	1	2	1	2	
MAX. WATTAGE			1,000	55	110	12	24	37	74	
MAX. LUMENS			22,000	3,000	6,000	960	1,920	2,373	4,746	
AVG. BULB LIFE (HRS.)	2,000		10,000		50,000		>30,000			
WIRE GUARD INCLUDED	Yes		Yes		Yes		No			
BULB INCLUDED	Yes		Yes		Yes		Yes			
LIGHT SOURCE ILLUMINATION LEVELS										
Measured Footcandles & Distance from Light Source (open area)	5' ft.	74.4	137.3	20.0	35.8	224.5	456.8	448.1	896	
	10' ft.	36.1	65.9	8.7	14.8	121.4	258.8	299	598	
	20' ft.	13.2	24.6	3.1	5.1	29.0	64.0	71	142	
	30' ft.	6.6	12.3	1.7	2.5	14.2	31.4	34	68	

## Task Lighting...



#### **ATTENTION**

Fluorescent and HID lamps contain mercury. Dispose of these lamps according to local, state, or federal laws. For further information on local, state, or other requirements for disposal of mercury-containing lamps, see http://www.lamprecycle.com.



Phone: 1-800-741-1258 Fax: 1-866-709-2802 Loadingdocksupply.com

# Portable Utility Lights

Incandescent, Fluorescent, and LED Series





#### **Features**

- Chip resistant safety yellow & black powder coating finish for high visibility and durability
- 15' long 18/3 SJT, 120V cordset with NEMA 15-5 grounded plug
- Shade will swivel 300° horizontally and 210° vertically
- On/Off switch, bulb, and wire guard included on each light head
- Made in U.S.A. with domestic and foreign components

#### Lamp Specifications - LED & FL

- Aluminum shade is 9-3/8" long with 7-3/4" diameter opening and will swivel 300° horizontally and 210° vertically
- LED 1 & 2 models are designed with an acrylic lens cover over each of the 12 single Watt LED emitters. Constructed with narrow 15° angle beam generating 960 lumens per bulb.
- FL models include a 55W spiral fluorescent bulb and internal reflector for maximum illumination at shorter distances.
- ETL C/US Listed for indoor & semi-protected outdoor use

#### Lamp Specifications - LED-37

RoHS

- Lexan housing
- · Safety glass front lens cover
- NEMA 4 rated enclosure
- · Can be used with dock arm, pedestal, cart, and tripod bases only.
- Push button on-off switch
- 15' power cord
- Compliant with RoHS 2 Directive (2011/65/EU), that of which includes the application exemptions outlined in Annex III of the directive.

#### Lamp Specifications - QH

- QH models include a 500 Watt quartz halogen bulb and weatherproof die cast aluminum light head with impact resistant lens
- Each shade size is 9" wide x 7-1/4" high x 9-3/4" deep
- ETL C/US listed for indoor & semi-protected outdoor use

#### Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	ТҮРЕ	DESCRIPTION	TOTAL MAX WATTS	# OF LIGHT HEADS	WT. (LBS)	LIST	
04885402	LED-37-1*		LED	37	1	6	340	
04885302	LED-37-2*	LIGHTHEAD	LED	74	2	10	688	
04873602	LED-1		LED	12	1	6	289	
04873702	LED-2		LED	24	2	9	644	
04803002	FL-1		FLUOREGGENE	55	1	5	206	
04803402	FL-2		FLUORESCENT	110	2	8	515	
04802902	QH-1			OLIA DEZ HALOGEN	500	1	5	129
04803302	QH-2		QUARTZ HALOGEN	1000	2	10	217	
04802702	PED	MOUNT/BASE	PEDESTAL			31	284	
04802802	CRT		CART			27	248	
04802302	TRI			TRIPOD			9	99
04802602	FLR		FLOOR			4	80	
04802402	CLP		CLAMP			2	44	
04802502	MAG		MAGNET			3	53	

<sup>\*</sup>Can be used with pedestal, cart, and tripod mounts only

### Individual Portable Light Components - Replacement Bulbs

MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	WATTS	USED WITH	WT. (LBS)	LIST
04850502	SSE-55	Fluorescent Bulb	55	ALL FL Light heads	1	54
04708502	LED-12	LED Bulb	12	ALL LED Light heads	1	110



Phone: 1-800-741-1258 Fax: 1-866-709-2802 Loadingdocksupply.com

## Heavy Duty Portable Utility Lights



### Quartz Halogen Light Heads

- (2) 500 Watt weatherproof die cast Aluminum light heads with 15' long, 3-conductor cord, and plug
- Quartz halogen lamps
- Impact resistant lens
- · On-Off switch
- OSHA approved wire guards and bulb included with each light head
- Made in U.S.A. with domestic and foreign components.



#### Cart Light Stand With GFCI Features

- Upright adjust from 5' to 8' high
- 10" diameter rubber wheels
- 15' all-weather, water and oil resistant SJTW 18/3 cordset and molded NEMA 5-15 plug
- Weatherproof electrical box with a 15 Amp GFCI duplex receptacle

### Tripod Light Stand Features

- Square 12 gauge steel tubing construction
- Adjustable legs fold up for storage, fold flat for sand bagging or can be set and locked at 6", 12", 18", or 24" ground clearances
- Height adjustable from 5' to 11' high
- Safety stop mechanism, at full extension, prevents the mast from being pulled out of the base
- 15' all-weather, water and oil resistant SJTW 18/3 cordset and molded NEMA 5-15 plug

#### Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	BASE TYPE	BULBS	WATTS	VOLTS	MAX LUMENS	AVE. BULB LIFE (HRS)	WT. (LBS)	LIST
04467802	PUL-1000Q-CD	CART	500W Quartz Halogen	1000	120	22,000	2,000	50	691
04468302	PUL-1000Q-TC	TRIPOD	300 w Quartz Halogen	1000				41	729



Phone: 1-800-741-1258 Fax: 1-866-709-2802 Loadingdocksupply.com