

DESCRIPTION

Category 6 Data Grade Keystone Jack 90° **Degree 8x8 Conductors.**

FEATURES

- Available in various colors for easy Identification
- 110-IDC Contacts (Terminal Block)
- Color Coded for 568A and 568B standards
- ANSI/TIA-568-C.2, ETL/UL Listed
- ISO/IEC11801 2nd edition EN50173 2nd edition
- Compatible with the I-Punch Termination tool
- Narrow connector allows high port density in small areas



Available in Black, Blue, Green, Gray, Ivory, Yellow, Red, White, Orange

V-MAX CAT6 DATA JACK **90° DEGREE STYLE**

SKU: 352-SERIES

Physical Specifications

Dimension (mm) Housing Material

Housing IDC Housing 19.86H x 17W x 31D

UL 94V-0 self extinguished plastic UL 94V-0 self extinguished plastic

Contact Material IDC 110 Contacts Nose Contacts Operating Life Compability

Phospor bronze, nickel plated 50µ Gold plating over nickel Minimum 750 Insertions 22 to 26 AWG Solid

FR-4, 1.6mm double sided

UL 94V-0 rated

PCB

Cap

Product Certifications

ANSI/TIA-568-C.2, FCC, 3P ETL Listed

Electrical:

Current Rating 1.5Amp Max 1000V RMS for 1min **Dielectric strength** Insulation resistance 500mΩ Contact resistance $20m\Omega$ DC resistance 0.1 Ohm -10°C to 60°C max **Temperature Range** 10%~90%; non condensing Humidity



Compatible with the I-Punch Termination Tool Sku# 078-2150





Rev. 09/2011 Subject to change without notice.