

# CAT6 HIGH GRADE 550MHz STP CMR RATED (SHIELDED)

Cat5eCableGuy.Com

## DESCRIPTION

Category-6, 23AWG, STP, 8C Solid Copper, 550MHz, Riser Rated, PVC Jacket 1000ft.

## FEATURES

- High-Performance Data Cable
- 550MHz Bandwidth for Data Applications, Fast Ethernet and 155Mbps TP-PMD/CDDI
- Category-6 Shielded Twisted Pair
- Easily Identified Color-Striped Pairs
- 23AWG Solid Bare Copper Conductors
- Exceeds EIA/TIA 568-B.2-1, ISO/IEC-11801
- Riser Rated (CMR)
- 1000ft Wooden Spool



36pcs per pallet  
(Packaging may vary)

## SKU: 062 SERIES

### Technical Data

Rated Temperature (°C)	70
Rated Voltage (V)	30
Product Standard Certification	CMR

### Conductor

**Solid Bare Copper**

Size 23 AWG

### Insulation

**PE**

Average Thickness (mm) 0.22

Min. Point Thickness (mm) 0.19

Insulation Diameter (±0.005mm) 1.01

Twisted Pair Diameter (±0.01) 2.02

Filler LDPE

Bond PE Tape

Shield AL-Foil

Drain Wire (TC) 0.40

### Assembly Diameter

**6.20**

### Jacket

**PVC**

Average Thickness (mm) 0.60

Min. Point Thickness (mm) 0.50

Outer Diameter (±0.10mm) 7.80

Rip Cord Yes

### Color of Pairs

Pair 1	Blue, White-Blue
Pair 2	Orange, White-Orange
Pair 3	Green, White-Green
Pair 4	Brown, White-Brown

### Mechanical Characteristics

Test Object	Jacket
Test Material	PVC
Before Tensile Strength (Mpa)	>=13.8
Aging Elongation (%)	>=100
Aging Condition (°Cxhrs)	100x168
After Tensile Strength (Mpa)	>=85% of unaged
Aging Elongation (%)	>=50% of unaged
Cold Bend (-20±2° Cx4hrs)	No Crack

### Marking on Jacket

VERTICAL 4001453 ETL VERIFIED CMR FT4 STP 4PR 23AWG  
CAT6 550MHz TIA/EIA-568B.2-1 RoHS XXXFT  
(SEQUENTIAL FOOT MARKERS ON JACKET)

Jacket color available in  
Blue, Black, White, Green, Gray, Red, Yellow



Cat5eCableGuy.Com  
Where Quality Cable is on Sale!



# CAT6 HIGH GRADE 550MHz STP CMR RATED (SHIELDED)


## PERFORMANCE

### Electrical Characteristics:

1.0-100MHz Impedance (Ohms)	100±15
100-250MHz Impedance (Ohms)	100±25
250-550MHz Impedance (Ohms)	100±35
1.0-100.0MHz Delay Skew (ns/100m)	<=45
Pair-to-Ground Capacitance Unbalance (pF/100m)	<=330
Max. Conductor DC Resistance 20°C (ohms/km)	95
Resistance Unbalance (%)	<=5

Frequency (Mhz)	Return Loss (Min dB)	Attenuation Max (dB/100m)	Next (Min dB)
0.772	19.4	1.8	76.0
1	20.0	2.0	74.3
4	23.0	3.8	65.3
8	24.5	5.3	60.8
10	25.0	6.0	59.3
16	25.0	7.6	56.2
20	25.0	8.5	54.8
25	24.3	9.5	53.3
31.25	23.6	10.7	51.9
62.5	21.5	15.4	47.4
100	20.1	19.8	44.3
200	18.0	29.0	39.8
250	17.3	32.8	38.3
350	16.3	39.8	36.1
450	15.5	46.0	34.5
550	14.9	51.7	33.2

Frequency (Mhz)	PSNext Min (dB)	ELFEXT Min(db/100m)	Delay Max(ns/100m)
0.772	74.0	70.0	-----
1	72.3	67.8	570.0
4	63.3	55.8	552.0
8	58.8	49.7	546.0
10	57.3	47.8	545.0
16	54.2	43.7	543.0
20	52.8	41.8	542.0
25	51.3	39.8	541.0
31.25	49.9	37.9	540.0
62.5	45.4	31.9	538.0
100	42.3	27.8	537.0
200	37.8	21.8	536.0
250	36.3	19.8	536.0
350	34.1	17.1	535.0
450	32.5	15.2	534.0
550	31.2	13.2	532.0



**Cat5eCableGuy.Com**  
Where Quality Cable is on Sale!

Rev. 01/2011

Subject to change without notice.