Return of the Legendary Gold Detector

GPX-4500

The versatile GPX-4500 has great performance on **all sizes of gold**, and penetrates mineralized ground **deeper** than all basic PI detectors.











- Two Coils Included
- Six Detect Modes
- Six Timings Options
- Five Ground Balance Settings















We Change People's Fortunes



18-inch Monoloop (P/N 3011-0075) 18-inch Double-D (P/N 3011-0079)



15 x 12-inch Double-D

11-inch Monoloop

(P/N 3011-0073) 11-inch Double-D



GPX Accessory Coils Find more gold of all sizes and


at all depths with a specialist

Commander accessory coil.

10 x 5-inch Double-D (P/N 3011-0076)



(P/N 3011-0072)





The Expert's Opinion...

"...the Minelab GPX-4500 represents the best value for somebody new to high power pulse induction nugget detecting and wanting to get in on it without mortgaging the farm..."

Steve Herschbach

Owner, Detector Prospector Forum www.detectorprospector.com





Timings For All Ground Conditions

6 Timings in 1 advanced detector



GPX Timings alter the transmit time periods and digital signal processing of MPS technology. Each of the six Timings is superior to a conventional single period Pulse Induction (PI) detector.

Detecting Functions General, Deep and Custom. Custom Modes are: **Detect Modes** Hi Mineral, Hi Trash, Patch and Test A Enhance, Normal, Sensitive Smooth, Salt **Timings** Course, Sensitive Extra and Sharp Tune (Noise Cancel) Automatic and Manual 0-255 Sensitivity Adjust Rx Gain 1-15 Discrimination Iron Reject: range 1-10 and All Metal Automatic Ground Balance, Fixed and Tracking: **Ground Balance** Slow, Medium and Fast **Ground Balance Type** General, Specific and Ground Balance Off **Pinpoint** Quick-Trak button Threshold Continuously variable 1-turn control **Target Volume Adjust** Volume Limit 1-20 **Key Technologies** MPS, DVT, SETA

Minelab®, GPX®, MPS™, DVT™, SETA™ and Commander™ are trademarks of Minelab Electronics Pty Ltd

Front and Rear Control Panels





Physical Specifications	
Coils (standard)	11" Double-D and 15"x12" Monoloop
Battery	Li-lon with built-in amplifier (up to 12 hrs) Supplied with mains and vehicle charger
Audio Output	6.3mm (1/4") headphone/speaker jack
Headphones	Koss 100 ohm headphones
Display	Monochrome LCD
Detector Weight	2.4kg (5.3lbs) (exluding battery)
Detector Length	1100mm-1300mm (43.3"-51.2")

To place an order or for more info, visit www.GoldRushTradingPost.com to find your nearest dealer

4907-0823-1

